

WHISPER Glamping Solution



Whisper, the place where dreams of a beautiful and luxurious summer holidays become a reality. The cottages, measuring $8m \times 3.20m$, are an oasis of harmony and relaxation. The cottage has been designed with maximum comfort and convenience in mind. The room height of 2.4 m and the flat ceiling give the interior a spacious and modern feel.



EQUIPMENT

SALON:

Sofa bed with sleeping function Air conditioning TV Table and chairs Electric heater

BATHROOM:

Cabinet with washbasin Mirror Shower enclosure Toilet bowl Electric finned radiator

KITCHEN:

Boiler 55 L Undercounter refrigerator Sink Electric hob 2-burner Telescopic hood

BEDROOM:

Double bed Bedside table Wardrobe Hanging locker Electric heater

CORRIDOR:

Wieszak na ubrania Rozdzielnia główna

*Pictures are for illustrative purposes only and do not constitute the subject of the offer. *Dimensions may vary with actual dimensions ± 3 cm.





PARAMETERS

External dimensions:	8 m x 3.20 m
Surface	21,38 m2 (hallway: 1,93 m2, living room: 10,53 m2, bedroom: 5,99 m2, bathroom: 2,93 m2)
usable area:	21,30 m² (nanway: $1,73$ m², nving room: $10,33$ m², bedroom: $3,77$ m², batmoom: $2,73$ m²)
Room height:	2,40 m, flat ceiling.
Design:	Steel frame with timber elements, constructed to structural design. Flat floor structure designed to be founded on footings. Single pitched roof. There are 4 cable eye bolt holes in the roof as standard for lifting and positioning the building. The use of a crane is required for foundation.
Floor:	In addition to steel construction elements, trapezoidal sheet metal, open-cell foam PUR 9 cm, wooden substructure, OSB board, PVC lining.
Roof and ceiling:	In addition to steel construction elements, timber substructure, 9 cm PUR open-cell foam, high-permeable membrane, seam sheeting. Flat ceiling in the cottage, covered with timber boarding, ceiling in the bathroom - PVC panels.
External walls:	Facade finished with timber boarding. In addition to steel construction elements, timber substructure, OSB board, 8,5 cm PUR open cell foam, windproof membrane and vapour barrier membrane.
Internal walls:	Timber structure, OSB , timber decking.
Doors:	Exterior 90/200 cm single leaf steel door, foam insulated, 48 mm thick U=1.3 W/(m²-K). Internal door 80/200 cm white MDF with wooden frame.
Windows:	5-chamber system, installation depth 70mm, double-glazed package with steel frame, white PVC profile with ventilators.
Guttering:	Steel gutters and downpipes.
Electrical installation:	Distribution box. Electrical conductors in peszel. For sockets 3 x 2,5 mm2 cable, for lighting 3 x 1,5 mm2. Electrical sockets, aerial, light switches. Socket under the cottage.
Installation Water and sewerage:	Installation in kitchen and bathroom made of ALU-PEX and PVC pipes. Hidden in the walls and routed under the bungalow for connection to the mains. Additional drain in the bathroom floor.
Ventilation:	Two-stage exhaust ventilation in the rooms with a wall fan located in the bathroom and ventilators in the windows to provide fresh air.
Interior lighting:	Ceiling lighting in the form of LED spots in each room.
Heating:	Electric oil radiators in each room. Plus an electric ribbed radiator in the bathroom.
Living room with kitchenette:	Fold-out sofa with sleeping area, TV/ aerial socket area, dining table with 3 chairs. Kitchen furniture in 18 mm furniture board with veneer. Recessed sink made of composite. Built-in kitchen with small under-counter fridge, telescopic extractor hood, 2-burner electric hob, and electric boiler. Countertop in the kitchen made of laminated chipboard. Internal air conditioning unit mounted on the wall.
Bedroom:	Double bed 160/200 cm with bedding container and removable mattress, bedside table, wall unit, free-standing wardrobe.
Bathroom:	80 × 80 cm square corner shower enclosure with sliding door, standing toilet bowl, round mirror, washbasin with cabinet.
Corridor:	Clothes hanger, and electrical distribution box.